

TB-60 Toilet Partition Cleaning and Maintenance

Maintenance: Given proper care, toilet partition doors, panels, and stile surfaces will retain their appearance for years. Periodic cleaning with a furniture polish is usually all that is required to keep them looking new.

Caution: DO NOT USE HOSE-DOWN CLEANING METHODS ON LAMINATED PLASTIC PRODUCTS *which have a wood product core . . . water directed onto the laminated plastic surface can be absorbed into the substrate causing swelling and possible delamination of the laminated plastic..*

TYPE OF SOIL	CLEANING AGENT	METHOD OF APPLICATION
Dirt, smudges, and fingerprints	Mild cleaning solution.	Wipe off soil using a cloth or sponge for smooth surfaces and a soft brush for textured surfaces. Rinse and dry.
Greasy soil, lipstick, crayon and oil	General purpose cleaner or mild degreaser.	Gently rub off soil using a cloth, sponge or soft bristle brush moistened in the cleaning agent. Rinse and dry.
Scaling or water marks	Bathroom cleaners containing phosphoric acid or acetic acids.	Gently rub off soil using a cloth, sponge or soft bristle brush moistened in the cleaning agent. Rinse or dry.
Graffiti	Bobrick Graffiti Remover part #891099 or equivalent.	Spray or wipe on, rub spots with soft cloth or sponge. Rinse and dry.

IMPORTANT INFORMATION:

Most stains can be completely removed with the cleaning methods listed. However, if the laminated plastic surface is scratched or badly worn, stains may be more difficult to remove and some may leave a ghosting effect.

The following substances should not be placed on any laminated plastic surface and any inadvertent spills must be wiped off immediately and rinsed thoroughly to avoid serious damage:

Sulfuric and nitric acids, hydrochloric and oxalic acids (used in liquid toilet bowl cleaners), bleaches, sodium hydroxide (used in lye and oven cleaners), and sodium hypo chlorite (used in laundry bleach).