











Bobrick's LED Mirror Collection brings high quality LEDs together with commercial grade mirror construction to provide a product that reflects quality, value and style.

AVAILABLE STANDARD SIZES AND STYLES:







B-1641 Series

B-1671 Series



B-1691 Series

STANDARD B-1641 MIRRORS

OVERALL SIZE					
MODEL NO.	W	Н	Lumens	Wattage	Availability
B-1641 2436	610mm	914mm	2,640	24	In stock
B-1641 2442	610mm	1067mm	2,900	26	In stock

STANDARD B-1671 MIRRORS

OVERALL SIZE					
MODEL NO.	W	Н	Lumens	Wattage	Availability
B-1671 2436	600mm	900mm	2,760	24	16 weeks
B-1671 2448	600mm	1200mm	3,310	29	In stock

Mirrors can be installed vertically or horizontally.

STANDARD B-1691 MIRRORS

OVERALL SIZE					
MODEL NO.	W	Н	Lumens	Wattage	Availability
B-1691 3040	762mm	1016mm	1,450	14	16 weeks

Special Order sizes available. Contact Bobrick for information: international@bobrick.com





FEATURES & BENEFITS

COMPETITIVE FEATURES	BOBRICK
CE Certification	CE-certified versions of these mirrors are specifically designed for international markets.
Safety Against Glass-Breakage	High safety via PVC-film-backed glass
AC-Connection (110-277 Volt)	Two CE-certified options; hard wiring and plugged. Included, 762mm cord with three-prong plug and an AC Adapter Kit with interchangeable plugs for the UK (type-G), Europe (type-C), and Australia (type-I).
Glass Thickness	5mm
Scratch Resistant	Gen 3 glass has high scratch resistance, also withstands salt spray test 4 times longer.
CRI* Overall Light Quality	90+ (excellent)
Warm Light Quality, 3000 Kelvin	Standard
Light/Power Efficacy	100+ Lumens/Watt (super efficient)
IP Rating	The mirror light engine is IP66 rated with an estimated 50,000-hour lifespan. Mounting panel are IP44 rated and exceeds ISO 9227:201, which passes 120-hour corrosion testing.
Sustainability	Eco-friendly lead-free silver backing

 $^{^*}$ CRI Colour Rendering Index - how accurately the mirror can produce a light that matches a naturally referenced light source, such as the sun.

