



^{*}PREMIUM COLORS CARRY AN UP-CHARGE NOT TO EXCEED 10% OF TOTAL COST.

PANELS OVER 60" WIDE WITH DIRECTIONAL PATTERNS AND FINISHES WILL BE SPLICED, JOINING THE 2 PIECES ON THE PARTICLE BOARD AT AN ADDITIONAL CHARGE.

HPL COLORS ARE PRINTED REPRODUCTIONS AND ARE FOR DESCRIPTIVE PURPOSES ONLY. REFER TO MANUFACTURER'S SAMPLES FOR ABSOLUTE COLOR FIDELITY. COLOR GUIDES AND SAMPLES ARE AVAILABLE FROM BOBRICK ON REQUEST.

RAPID FRESPONSE: LEAD-TIME FOR 35 STANDARD COLORS, ON ORDERS OF UP TO 15 COMPARTMENTS, IS 2 BUSINESS DAYS FOR 1550/1540 AND 10 BUSINESS DAYS FOR 1530/1040/1030 AFTER ORDER APPROVAL.

LEAD-TIME FOR A SUBSTANTIAL SELECTION OF STOCKED WILSONART®, FORMICA®, NEVAMAR®, AND PIONITE® COLORS, ON ORDERS OF UP TO 15 COMPARTMENTS, IS 5 BUSINESS DAYS FOR 1550/1540 AND 20 BUSINESS DAYS FOR 1530/1040/1030 AFTER ORDER APPROVAL.

ECONOMICAL

HPL (HIGH PRESSURE LAMINATE) SATISFIES ALL BUDGETS




DURABLE

HPL OUTPERFORMS METAL PARTITIONS







COMPLIANT

HPL COMPLIES WITH FIRE CODE AND SAFETY STANDARDS

ALL HPL PARTITIONS MEET CLASS B ASTM E 84 INTERIOR WALL FINISH CLASSIFICATION. DOOR HARDWARE CONFORMS TO EMERGENCY ACCESS STANDARDS AND IS OPERABLE WITH ONE HAND, WITHOUT TIGHT GRASPING, PINCHING, OR TWISTING OF THE WRIST, AND DOES NOT EXCEED FIVE POUNDS OF FORCE.

SUSTAINABLE

HPL QUALIFIES FOR LEED CREDITS

CLASSIFICATION	SECTION
RECYCLED CONTENT	MR 4.1/4.2
RAPIDLY RENEWABLE MATERIALS	MR 6.0
CERTIFIED WOOD	MR 7.0
LOW EMITTING MATERIALS	EQ 4.1
REGIONAL MATERIALS*	MR 5.1

^{*} IF SHIPPED WITHIN 500 MILES OF BOBRICK'S THREE PRODUCTION FACILITIES.

HPLSERIES HPL PRODUCT OVERVIEW

	HARDWARE	EDGE FINISH
HPL Metro™ 1550	CONCEALED CHROME-PLATED	HPL
HPL Classic™ 1540	CHROME-PLATED	HPL
HPL Accent™ 1530	CONCEALED STAINLESS STEEL	STAINLESS STEEL
STEEL CORE STILE OPTION		
DESIGNER 1040	CONCEALED STAINLESS STEEL	HPL
TRIMLINE 1030	CONCEALED STAINLESS STEEL	STAINLESS STEEL
MAXIMUM HEIGHT/STEEL CORE STILE OPTION		
DESIGNER 2040	CONCEALED STAINLESS STEEL	HPL
TRIMLINE 2030	CONCEALED STAINLESS STEEL	STAINLESS STEEL

NOTE: ALL SERIES ARE AVAILABLE IN FLOOR-ANCHORED, OVERHEAD-BRACED AND CEILING-HUNG CONFIGURATIONS. REFER TO WWW.BOBRICK.COM FOR SPECIFICATION DETAILS, TECHNICAL BULLETINS, MODEL NUMBERS, UPGRADES AND OPTIONS.



^{*}PER ASTM TEST METHODOLOGY, RESULTS ON FILE.